

Performance

Flow (CFM)

Size ⁽¹⁾	Model	HP	RPM ⁽²⁾	Voltage ⁽³⁾	Steel ⁽⁴⁾	Nylon ⁽⁴⁾	Cast Alum. ⁽⁴⁾
12	C12A	.33	1800	250V DC	1523	1950	1940
	C12B	.33	1765	208-230/460/3/60 VAC	1493	2060	1760
	C12C	.33	1735	115/208-230/1/60 VAC	1468	2020	1870
16	C16A	.33	1800	250V DC	2915	3190	3190
	C16B	.33	1765	208-230/460/3/60 VAC	2938	3310	3390
	C16C	.33	1735	115/208-230/1/60 VAC	2888	3250	3340
18	C18A	.33	1800	250V DC	3233	3920	3920
	C18B	.33	1765	208-230/460/3/60 VAC	3170	3840	3840
	C18C	.33	1735	115/208-230/1/60 VAC	3116	3780	3780
20	C20A	.33	1800	250V DC	3392	4080	4080
	C20B	.33	1765	208-230/460/3/60 VAC	3368	3990	3990
	C20C	.33	1735	115/208-230/1/60 VAC	3396	3930	3930
24	C24B1	1	1765	208-230/460/3/60 VAC	7485	7960	8080
	C24C1	1	1745	115/208-230/1/60 VAC	7593	7860	7970

Model Legend Key

C
Fan Type
12
Fan Blade Diameter
A
250V DC
-SB
Mounting Option

Custom Finishes Include

Hot Dipped Galvanized
 Aluminum
 304 Stainless Steel
 316 Stainless Steel

Notes

(1) Size of the fan blade
 (2) Two speed & variable speed options available
 (3) 50Hz & 575V available
 (4) Fan blade material. Galvanized steel is standard

Additional Notes

