

3 Phase

Flow (CFM)

Size ⁽¹⁾	Model	HP	RPM ⁽²⁾	Voltage ⁽³⁾	Steel ⁽⁴⁾	Nylon ⁽⁴⁾	Cast Alum. ⁽⁴⁾
18	T18B.33	.33	1765	208-230/460/3/60 VAC	3122	3840	3840
	T18B.75	.75	1755	208-230/460/3/60 VAC	4554	5100	5100
20	T20B.5	.5	1760	208-230/460/3/60 VAC	3924	5410	5410
	T20B.5X	.5	1160	208-230/460/3/60 VAC	4150	4930	4920
	T20B1	1	1765	208-230/460/3/60 VAC	5596	6640	6640
24	T24B.5X	.5	1160	208-230/460/3/60 VAC	5952	6630	6630
	T24B1	1	1765	208-230/460/3/60 VAC	7485	8080	8080
	T24B1.5	1.5	1750	208-230/460/3/60 VAC	8257	9240	9240
	T24B2	2	1745	208-230/460/3/60 VAC	9730	10300	10300
30	T30B2	2	1745	208-230/460/3/60 VAC	12456	13500	13600
	T30B3	3	1765	208-230/460/3/60 VAC	14326	16600	16700
	T30B5	5	1750	208-230/460/3/60 VAC	17807	19700	19700
36	T36B5	5	1750	208-230/460/3/60 VAC	20268	24400	24400
42	T42B7.5X	7.5	1175	208-230/460/3/60 VAC	30962	34700	34700

1 Phase

Flow (CFM)

Size ⁽¹⁾	Model	HP	RPM ⁽²⁾	Voltage ⁽³⁾	Steel ⁽⁴⁾	Nylon ⁽⁴⁾	Cast Alum. ⁽⁴⁾
18	T18C.33	.33	1735	115/208-230/1/60 VAC	3069	3770	3770
	T18C.75	.75	1745	115/208-230/1/60 VAC	4528	5070	5070
20	T20C.5	.5	1730	115/208-230/1/60 VAC	4148	5330	5330
	T20C1	1	1745	115/208-230/1/60 VAC	5611	6550	6550
24	T24C1	1	1745	115/208-230/1/60 VAC	7593	7700	7700
	T24C2	2	1750	115/208-230/1/60 VAC	9535	10300	10300
30	T30C2	2	1750	115/208-230/1/60 VAC	12492	13500	13600
	T30C5	5	1730	208-230/460/1/60 VAC	17603	20000	20000
36	T36C5	5	1730	208-230/460/1/60 VAC	20036	24900	24900
	T36C3X	3	1160	208-230/460/1/60 VAC	18263	20900	20900

Model Legend Key

T
Fan Type

24
Fan Blade Diameter

C
1PH, VAC

1
Motor HP

-
RPM Code
1800 Series

-PT
Mounting Option

Custom Finishes Include

Hot Dipped Galvanized
Aluminum
304 Stainless Steel
316 Stainless Steel

Notes

(1) Size of the fan blade
(2) Two speed & variable speed options available
(3) 50Hz & 575V available
(4) Fan blade material. Galvanized steel is standard